

Responder Spec Sheet

Power Distribution

- Integrated Power and Grounds
- Direct to Battery Power and Grounds
- 125 amp Continuous Service with Master Switch
- Central Fuse and Relay Panel
- Lighting Selector Panel
- Up to 32 fused outputs

Main Harness

- Fabricated Wire Harness
- Color Coded and Heat Stamped every 6 – 14 inches
- Temperature Rated at – 40C(-40F) to 125C(257F)
- Max Load Tested at –40f to 221f
- 10,000 Rub, Fire Retardant 40 Mil Protective Loom
- TXL wire Meets or exceeds SAE Requirements J-1128
- 40 Mil Loom constructed of composite fiberglass and PVC materials
- Quick Disconnect: Console Components, Grill lights, Siren, Speaker, Wig Wag, and Flashers
- Reduces RFI and Component to Component Interference
- Designed for the purpose
- Whelen CenCom, B-Link
- Federal SS2000
- Traditional Low and High Current Console switching

Auxiliary Harness Options

- Lightbar Quick Disconnect
- Dash & Visor Lighting or Mirror & Mid-ship Lighting
- 40 Amp Relay Expansion Kit
- DR33 MNSTAR Timer for Delayed Power Cutoff
- Component Direct Plug in
- Ignition Hot Circuit
- Dual Radio Harness Option